

**TMA-1240
L TYPE ROCK
TEST HAMMER**



AGGREGATE

L Type Rock Test Hammer



PRODUCT MODEL

TMA-1240 | L Type Rock Test Hammer

STANDARDS

EN 12504-2 | ASTM C805

INFORMATION

Manufacturer : TESTMAK INS.LAB.MAK.SAN.VE TİC. PAZ. İTH. İHR. LTD. STİ

Country of Origin : TURKEY

Product name: L Type Rock Test Hammer

Code of product: TMA-1240

DESCRIPTION

The spring drives the flip hammer; the flip hammer knock on the surface of brick through flip rod; the restoring force produced after instant transform makes the hammer rebound back, and the pointer indicates the instance of rebound, which is one of a indicators evaluating brick's compressive strength and predict the compressive resistance and label

L Type Rock Test Hammer

of the brick. It is used for testing strength of ordinary bricks with NDE, still for testing strength of light skeletal material concrete and other light materials.

Specifications:

- L type
- Nominal power: 0.735J Strike length of flip hammer: 75 ± 0.3 mm
- Friction of pointer slider: 0.5 ± 0.1 N Work length of flip tensioned spring: $61.5.0\pm 0.3$ mm
- Fixed value of steel anvil: 74 ± 2
- Location of flip hammer's hook release: "100" at the scale mark Sphere semi-diameter at the end of the flip rod: 25 ± 1 mm
- Aluminium frame
- Carrying Case made of special leather
- Carborundum stone for abrasive
- Spare Test Spring
- Phillips screwdriver
- Flat screwdriver

TECHNICAL SPECIFICATIONS

Dimensions	330x170x85 mm
Weight	1,4 kg



TESTMAK
MATERIAL TEST EQUIPMENTS

Telephone : +90 312 395 36 42
Fax : +90 312 395 36 01

Website : www.testmak.com
E-Mail : info@testmak.com

Koca Sinan Industrial Sites 1183 Street No:
40 06370 OSTIM / ANKARA / TURKEY